

# SAFETY DATA SHEET

Date Issued : 2/23/2010  
MSDS No : RMA - Wand  
Date Revised : 5/5/2015  
Revision No : 2

## Qualitek® RMA Rework Wand

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Qualitek® RMA Rework Wand

**PRODUCT DESCRIPTION:** RMA Rework Wand

#### MANUFACTURER

Qualitek International, Inc.  
315 Fairbank St.  
Addison, IL 60101  
**Emergency Phone:** (800) 535-5053  
**Service Number:** (630) 628-8083

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac  
1-352-323-3500 Outside the U.S.

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Eye Irritation, Category 2A

#### GHS LABEL



Exclamation  
mark

#### SIGNAL WORD: WARNING

#### HAZARD STATEMENTS

H319: Causes serious eye irritation.

#### PRECAUTIONARY STATEMENT(S)

##### Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

##### Disposal:

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

#### POTENTIAL HEALTH EFFECTS

**EYES:** Irritating, and may injure eye tissue if not removed promptly.

**SKIN:** Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

# SAFETY DATA SHEET

Date Issued : 2/23/2010

MSDS No : RMA - Wand

Date Revised : 5/5/2015

Revision No : 2

## Qualitek® RMA Rework Wand

**INGESTION:** Minimal toxicity. Small amounts of the liquid aspirated into the respiratory system during ingestion, or from vomiting, may cause bronchiopneumonia or pulmonary edema.

**INHALATION:** High vapor concentrations are irritating to the eyes, nose throat and lungs. May cause headaches and dizziness and may have other central nervous system effects. Negligible hazard at ambient temperature (-18 to 38°C).

**CARCINOGENICITY:** This product contains no components at concentrations of 0.1 percent or greater that are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
2-Propanol	< 65	67-63-0
Rosin (Non-hazardous)	< 35	8050-09-7

### 4. FIRST AID MEASURES

**EYES:** Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. Get medical attention as soon as possible.

**INGESTION:** If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

**INHALATION:** Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Stinging, tearing, redness and swelling.

**SKIN:** Redness, burning, drying, cracking and rash.

**INGESTION:** Nausea, vomiting, impaired coordination, diarrhea, dizziness, drowsiness, weakness, fatigue, headache and loss of consciousness.

**NOTES TO PHYSICIAN:** If symptoms such as loss of gag reflex, convulsions, or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered. Metabolism of isopropanol forms acetone, which may be detected in the urine or expired air. In contrast to diabetic acidosis, acidosis will occur in the absence of hyperglycemia. Hemodialysis should be considered in severe acute intoxications.

**COMMENTS:** If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this MSDS to the physician/health care professional.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Alcohol foam, carbon dioxide, or dry chemical.

# SAFETY DATA SHEET

Date Issued : 2/23/2010

MSDS No : RMA - Wand

Date Revised : 5/5/2015

Revision No : 2

## Qualitek® RMA Rework Wand

**HAZARDOUS COMBUSTION PRODUCTS:** May include carbon monoxide and carbon dioxide.

**FIRE FIGHTING PROCEDURES:** Either allow fire to burn under controlled conditions or extinguish with alcohol type foam and dry chemical. Try to cover liquid spills with foam. Use water spray to cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

**FIRE FIGHTING EQUIPMENT:** Self contained breathing apparatus and full protective turn-out gear.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent. Consult an expert on disposal of recovered materials and ensure conformity to local disposal regulations.

**LARGE SPILL:** If in public area, keep public away and advise authorities. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent. Consult Section 13 for disposal information.

### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** In the event of a water spill, eliminate all sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request that all stay clear.

**LAND SPILL:** In the event of a land spill, prevent liquid from entering sewers, watercourses, or low areas.

### 7. HANDLING AND STORAGE

**HANDLING:** Keep container closed. Handle and open containers with care. DO NOT handle near an open flame, heat, or other sources of ignition. DO NOT pressurize, cut, heat, or weld containers. Empty product containers may contain product residue. DO NOT reuse empty containers without commercial cleaning or reconditioning.

**STORAGE:** Store in a cool, well ventilated place away from incompatible materials. Do not store near an open flame, heat, or other source of ignition. Protect materials from direct sunlight.

**ELECTROSTATIC ACCUMULATION HAZARD:** Use proper grounding and bonding procedures when transferring material.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Provide general and/or local exhaust ventilation to control airborne levels below the OSHA/ACGIH exposure guidelines.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear splash goggles or glasses with face shield.

**SKIN:** Neoprene rubber gloves, impermeable gloves, cuffed butyl-rubber gloves, or nitrile rubber gloves.

**RESPIRATORY:** Atmospheric levels should be maintained below the exposure guideline. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures and/or without sufficient ventilation, use a NIOSH/MSHA approved air-purifying respirator.

# SAFETY DATA SHEET

Date Issued : 2/23/2010

MSDS No : RMA - Wand

Date Revised : 5/5/2015

Revision No : 2

## Qualitek® RMA Rework Wand

**PROTECTIVE CLOTHING:** Protective clothing and safety shoes as necessary to minimize contact.

**WORK HYGIENIC PRACTICES:** Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

**OTHER USE PRECAUTIONS:** Eye wash station and quick drench safety shower in immediate work area.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** Mild ethereal odor.

**APPEARANCE:** Liquid

**COLOR:** Light amber.

**AUTOIGNITION TEMPERATURE:** 456°C (852°F)

**VAPOR PRESSURE:** 33 mmHg at 20°C (68°F)

**BOILING POINT:** 82°C (180°F)

**MELTING POINT:** Not Applicable

**SOLUBILITY IN WATER:** Partially Soluble

**EVAPORATION RATE:** < 2.3 (n-Butyl Acetate=1)

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable under ordinary use and storage conditions.

**POLYMERIZATION:** May occur.

**CONDITIONS TO AVOID:** Ignition sources such as sparks and open flames.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May emit toxic fumes of carbon monoxide and carbon dioxide.

**INCOMPATIBLE MATERIALS:** Caustics, amines, alkanamines, aldehydes, strong oxidizing agents, and chlorinated compounds.

### 11. TOXICOLOGICAL INFORMATION

**GENERAL COMMENTS:** No toxicological information available at this time.

### 12. ECOLOGICAL INFORMATION

**GENERAL COMMENTS:** No information on ecological toxicity or biodegradability is available at this time.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

# SAFETY DATA SHEET

Date Issued : 2/23/2010

MSDS No : RMA - Wand

Date Revised : 5/5/2015

Revision No : 2

## Qualitek® RMA Rework Wand

**EMPTY CONTAINER:** Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or otherwise properly disposed of.

**GENERAL COMMENTS:** This substance, when discarded or disposed of, could be hazardous waste according to Federal regulations (40 CFR 261) due to its characteristic of ignitability (D001). The transportation, storage, and disposal of this waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Disposal can occur only in properly permitted facilities. Check state and local regulations for any additional requirements, as these may be more restrictive than federal laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in the MSDS incomplete, inaccurate or otherwise inappropriate.

### 14. TRANSPORT INFORMATION

**DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Not regulated by DOT

### 15. REGULATORY INFORMATION

**UNITED STATES**

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** Acute health, chronic health and fire hazard.

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** Not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA).

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**CALIFORNIA PROPOSITION 65:** When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

**CANADA**

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** WHMIS Hazardous Ingredients: 2-Propanol

**WHMIS CLASS:** Class B Division 2, Class D Division 2B

### 16. OTHER INFORMATION

**REASON FOR ISSUE:** New format

**APPROVED BY:** P. Han    **TITLE:** Technical Director

**PREPARED BY:** J. Saleda-Layton

# SAFETY DATA SHEET

Date Issued : 2/23/2010

MSDS No : RMA - Wand

Date Revised : 5/5/2015

Revision No : 2

## Qualitek® RMA Rework Wand

**INFORMATION CONTACT:** (630) 628-8083

**REVISION SUMMARY:** This MSDS replaces the 2/18/2013 MSDS. Revised: **Section 1:** REASON FOR ISSUE. **Section 5:** GENERAL HAZARD. **Section 9:** FLAMMABLE LIMITS, FLASH POINT AND METHOD, SPECIFIC GRAVITY, VAPOR DENSITY. **Section 12:** ECOTOXICOLOGICAL INFORMATION. **Section 14:** DOT (DEPARTMENT OF TRANSPORTATION) ( TECHNICAL NAME, PRIMARY HAZARD CLASS/DIVISION, UN/NA NUMBER, PACKING GROUP, PLACARDS, LABEL ). **Section 16:** HMIS RATING ( PERSONAL PROTECTION ).

### HMIS RATING

<b>HEALTH</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY</b>		<b>0</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>

**MANUFACTURER DISCLAIMER:** The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Material Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Material Safety Data Sheets as a source of hazards information and response.