

# SAFETY DATA SHEET

Date Issued : 4/21/2005

MSDS No : PF708

Date Revised : 4/21/2015

Revision No : 3

## Qualitek® Water Soluble Paste Flux PF708

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Qualitek® Water Soluble Paste Flux PF708**PRODUCT DESCRIPTION:** Water Soluble Paste Flux**MANUFACTURER**

Qualitek International, Inc.

315 Fairbank St.

Addison, IL 60101

**Emergency Phone:** (800) 535-5053**Service Number:** (630) 628-8083**24 HR. EMERGENCY TELEPHONE NUMBERS**

1-800-535-5053 Infotrac

1-352-323-3500 Outside the U.S.

### 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Eye Irritation, Category 2A

**GHS LABEL**Exclamation  
mark**SIGNAL WORD:** WARNING**HAZARD STATEMENTS**

H319: Causes serious eye irritation.

**PRECAUTIONARY STATEMENT(S)****Prevention:**

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash hands thoroughly after handling.

**Response:**

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

**Disposal:**

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

# SAFETY DATA SHEET

Date Issued : 4/21/2005

MSDS No : PF708

Date Revised : 4/21/2015

Revision No : 3

## Qualitek® Water Soluble Paste Flux PF708

### POTENTIAL HEALTH EFFECTS

**EYES:** Fumes from this and other soldering products may cause eye irritation.

**INGESTION:** Ingestion of this or other soldering products may cause headache, nausea, and muscular pain.

**INHALATION:** Inhalation of the fumes from this or other soldering products may cause headache, nausea and muscular pain.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Amines, tallow alkyl, ethoxylated	< 40	61791-26-2
Diethylene Glycol Dibutyl Ether	< 30	112-73-2

### 4. FIRST AID MEASURES

**EYES: MOLTEN PRODUCT:** Cool burns with plenty of low-pressure water. Get immediate medical attention.

**SOLID PRODUCT:** Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation develops.

**SKIN: MOLTEN PRODUCT:** Immediately cool skin burns with water and cold packs for at least 15 minutes. Do not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. **SOLID PRODUCT:** Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

**INGESTION:** If victim is conscious, give several glasses of water and keep the airway clean. Get medical attention.

**INHALATION:** Move person to fresh air. If breathing is stopped or is labored, give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be used. Get medical attention.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**CHRONIC EFFECTS:** Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain. Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and damage to the mucous membranes.

**COMMENTS:** If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this MSDS to the physician/health care professional.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical or appropriate foam. Water may be effective for cooling containers but not for extinguishing.

**EXPLOSION HAZARDS:** Closed containers may explode when exposed to fire conditions.

**FIRE FIGHTING EQUIPMENT:** Self contained breathing apparatus and full protective turn-out gear.

# SAFETY DATA SHEET

Date Issued : 4/21/2005

MSDS No : PF708

Date Revised : 4/21/2015

Revision No : 3

## Qualitek® Water Soluble Paste Flux PF708

### 6. ACCIDENTAL RELEASE MEASURES

**GENERAL PROCEDURES:** Scoop up material and deposit in appropriate containers. Clean up residual spill area with isopropanol or detergent water.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Store in a cool dry place away from incompatible materials. Keep away from heat, flame, sparks and other sources of ignition. Keep containers closed when not in use.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Local exhaust may be necessary if working with the product in enclosed areas or at elevated temperatures.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Face shield, safety glasses with side shield or chemical splash goggles.

**SKIN:** Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

**RESPIRATORY:** Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.

**PROTECTIVE CLOTHING:** Protective clothing and safety shoes as necessary to minimize contact.

**WORK HYGIENIC PRACTICES:** Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

**OTHER USE PRECAUTIONS:** Eye wash station and quick drench safety shower in immediate work area.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** Mild.

**APPEARANCE:** Smooth amber paste.

**pH:** 6.00 to 7.00

**FLASH POINT AND METHOD:** > 204°C (400°F)

**FLAMMABLE LIMITS:** N/E

**AUTOIGNITION TEMPERATURE:** > 227°C (440°F)

**VAPOR PRESSURE:** Not Determined

**VAPOR DENSITY:** Not Determined

**BOILING POINT:** 300°C (572°F) @ 760 mmHg

**MELTING POINT:** > 100°C (212°F)

**SOLUBILITY IN WATER:** Complete

# SAFETY DATA SHEET

Date Issued : 4/21/2005

MSDS No : PF708

Date Revised : 4/21/2015

Revision No : 3

## Qualitek® Water Soluble Paste Flux PF708

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable.

**POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Under fire conditions carbon dioxide and carbon monoxide may be evolved.

**INCOMPATIBLE MATERIALS:** Strong acids and strong oxidizers should be avoided..

### 11. TOXICOLOGICAL INFORMATION

#### CARCINOGENICITY

**IARC:** Not listed.

**NTP:** Not listed.

**OSHA:** Not listed.

### 12. ECOLOGICAL INFORMATION

**GENERAL COMMENTS:** No information on ecological toxicity or biodegradability is available at this time.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not regulated by DOT

### 15. REGULATORY INFORMATION

#### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** Not considered a hazard.

**313 REPORTABLE INGREDIENTS:** None.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS:** All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**CALIFORNIA PROPOSITION 65:** When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

# SAFETY DATA SHEET

**Date Issued :** 4/21/2005  
**MSDS No :** PF708  
**Date Revised :** 4/21/2015  
**Revision No :** 3

## Qualitek® Water Soluble Paste Flux PF708

### 16. OTHER INFORMATION

**REASON FOR ISSUE:** New format

**APPROVED BY:** P. Han    **TITLE:** Technical Director

**PREPARED BY:** J. Saleda-Layton

**INFORMATION CONTACT:** (630) 628-8083

**REVISION SUMMARY:** This MSDS replaces the 2/13/2013 MSDS. Revised: **Section 1:** APPROVED BY, 24 HR. EMERGENCY TELEPHONE NUMBERS, PREPARED BY, REASON FOR ISSUE, TITLE. **Section 2:** POTENTIAL HEALTH EFFECTS - SKIN. **Section 14:** SHIPPING NAME.

#### HMIS RATING

<b>HEALTH</b>	<input type="checkbox"/>	<b>2</b>
<b>FLAMMABILITY</b>	<input type="checkbox"/>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<input type="checkbox"/>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<input type="checkbox"/>	<b>B</b>

**MANUFACTURER DISCLAIMER:** The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Material Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Material Safety Data Sheets as a source of hazards information and response.